


## MODEL 7721 MECHANICAL TEE, FEMALE THREADED OUTLET

The Model 7721 Mechanical Tee when mounted on hole cut pipe provides a fast and easy mid-pipe threaded branch outlet. By utilizing the Model 7721 you eliminate the need for welding or the use of multiple fittings. The Mechanical Tee is comprised of upper and lower ductile iron housing segments, a grade "E" EPDM rubber molded gasket and plated track bolts and nuts. Mechanical tees are supplied with our standard painted finishes, i.e. orange or RAL3000 red. Optional finishes such as hot dipped zinc galvanized and custom epoxy coatings are also available.



For Fire Protection pressure rating, listing, and approval information, refer to Data Sheet B-42 or visit **SHURJOINT** website, [www.shurjoint.com](http://www.shurjoint.com) for details or contact your **SHURJOINT** Representative.



Full warranty terms can be found on [www.shurjoint.com](http://www.shurjoint.com)

**Model 7721 Mechanical Tee, Female Threaded Outlet**

Nominal Size Run x Branch	Max. Working Pressure (CWP)* PSI Bar	Hole Dia. $\pm$ +0.13, -0 / - +3.2, -0		Dimensions					Bolt Size	Weight Lbs Kgs
		T#	A	B	C	D				
in mm		in mm	in mm	in mm	in mm	in mm	in mm	in mm	in mm	
2 x 1/2 50 x 15	300 20	1.50 38	1.97 50	2.50 64	1.57 40	5.04 128	2.87 73	3/8 x 2 1/8 M10 x 55	2.4 1.1	
2 x 3/4 50 x 20	300 20	1.50 38	1.97 50	2.50 64	1.57 40	5.04 128	2.87 73	3/8 x 2 1/8 M10 x 55	2.4 1.1	
2 x 1 50 x 25	300 20	1.50 38	2.00 51	2.68 68	1.57 40	5.04 128	2.87 73	3/8 x 2 1/8 M10 x 55	2.6 1.2	
2 x 1 1/4 50 x 32	300 20	1.75 45	2.08 53	2.80 71	1.57 40	5.04 128	3.22 82	3/8 x 2 1/8 M10 x 55	2.9 1.3	
2 x 1 1/2 50 x 40	300 20	1.75 45	2.08 53	2.80 71	1.57 40	5.04 128	3.22 82	3/8 x 2 1/8 M10 x 55	2.9 1.3	
2 1/2 x 1/2 65 x 15	300 20	1.50 38	2.25 57	2.80 71	1.89 48	5.75 146	2.87 73	1/2 x 3 M12 x 75	3.1 1.4	
2 1/2 x 3/4 65 x 20	300 20	1.50 38	2.32 59	2.88 73	1.89 48	5.75 146	2.87 73	1/2 x 3 M12 x 75	3.1 1.4	
2 1/2 x 1 65 x 25	300 20	1.50 38	2.28 58	2.95 75	1.89 48	5.75 146	2.87 73	1/2 x 3 M12 x 75	3.3 1.5	
2 1/2 x 1 1/4 65 x 32	300 20	2.00 51	2.40 61	3.11 79	1.89 48	5.75 146	3.22 82	1/2 x 3 M12 x 75	3.5 1.6	
2 1/2 x 1 1/2 65 x 40	300 20	2.00 51	2.40 61	3.11 79	1.89 48	5.75 146	3.22 82	1/2 x 3 M12 x 75	3.5 1.6	
3 x 1/2 80 x 15	300 20	1.50 38	2.47 63	3.19 81	2.20 56	6.39 160	2.63 67	1/2 x 3 M12 x 75	3.5 1.6	
3 x 3/4 80 x 20	300 20	1.50 38	2.44 62	3.07 78	2.09 53	6.30 160	2.76 70	1/2 x 3 M12 x 75	3.5 1.6	
3 x 1 80 x 25	300 20	1.50 38	2.50 64	3.19 81	2.20 56	6.39 160	2.63 67	1/2 x 3 M12 x 75	3.7 1.7	
3 x 1 1/4 80 x 32	300 20	2.00 51	2.80 71	3.50 89	2.20 56	6.39 160	3.46 88	1/2 x 3 M12 x 75	4.2 1.9	
3 x 1 1/2 80 x 40	300 20	2.00 51	2.80 71	3.50 89	2.20 56	6.39 160	3.46 88	1/2 x 3 M12 x 75	4.4 2.0	
3 x 2 80 x 50	300 20	2.50 64	2.83 72	3.58 91	2.20 56	6.39 160	3.98 101	1/2 x 3 M12 x 75	5.1 2.3	

**Model 7721 Mechanical Tee, Female Threaded Outlet**

Nominal Size Run x Branch	Max. Working Pressure (CWP)* PSI Bar	Hole Dia. F +0.13, -0 / - +3.2, -0	T#	Dimensions				Bolt Size	Weight
				A	B	C	D		
in mm		in mm	in mm	in mm	in mm	in mm	in mm	in mm	Lbs Kgs
4 x ½ 100 x 15	300 20	1.50 38	3.00 76	3.70 94	2.83 72	7.48 190	2.63 67	½ x 3 M12 x 75	4.2 1.9
4 x ¾ 100 x 20	300 20	1.50 38	2.95 75	3.58 91	2.68 68	7.48 190	2.91 74	½ x 3 M12 x 75	4.2 1.9
4 x 1 100 x 25	300 20	1.50 38	3.03 77	3.70 94	2.83 72	7.48 190	2.63 67	½ x 3 M12 x 75	4.4 2.0
4 x 1¼ 100 x 32	300 20	2.00 51	3.19 81	3.89 99	2.83 72	7.48 190	3.35 85	½ x 3 M12 x 75	4.8 2.2
4 x 1½ 100 x 40	300 20	2.00 51	3.19 81	3.89 99	2.83 72	7.48 190	3.35 85	½ x 3 M12 x 75	5.1 2.3
4 x 2 100 x 50	300 20	2.50 64	3.38 86	4.13 105	2.83 72	7.48 190	3.98 101	½ x 3 M12 x 75	5.9 2.7
4 x 2½ 100 x 65	300 20	2.75 70	3.23 82	4.37 111	2.83 72	7.48 190	4.40 112	½ x 3 M12 x 75	7.3 3.3
4 x 3 100 x 80	300 20	3.50 89	3.23 82	4.40 112	2.83 72	7.48 190	5.35 136	¾ x 3½ M16 x 90	12.3 5.6
5 x 2 125 x 50	300 20	2.50 64	4.13 105	4.88 124	3.39 86	9.29 236	4.00 102	¾ x 3½ M16 x 90	9.2 4.2
5 x 2½ 125 x 65	300 20	2.75 70	3.89 99	5.00 127	3.39 86	9.29 236	4.65 118	¾ x 3½ M16 x 90	9.9 4.5
6 x ½ 150 x 15	300 20	2.00 51	4.48 114	4.96 126	3.78 96	10.24 260	3.54 90	5/8 x 5 5/16 M16 x 135	9.7 4.4
6 x 1 150 x 25	300 20	2.00 51	4.33 110	5.00 127	3.86 98	10.07 256	3.50 89	5/8 x 5 5/16 M16 x 135	9.7 4.4
6 x 1¼ 150 x 32	300 20	2.00 51	4.29 109	5.00 127	3.86 98	10.07 256	3.66 93	5/8 x 5 5/16 M16 x 135	9.7 4.4
6 x 1½ 150 x 40	300 20	2.00 51	4.29 109	5.00 127	3.86 98	10.07 256	3.66 93	5/8 x 5 5/16 M16 x 135	9.7 4.4
6 x 2 150 x 50	300 20	2.50 64	4.45 113	5.29 132	3.86 98	10.07 256	3.98 101	5/8 x 5 5/16 M16 x 135	10.6 4.8
6 x 2½ 150 x 65	300 20	2.75 70	4.37 111	5.50 140	3.86 98	10.07 256	4.65 118	5/8 x 5 5/16 M16 x 135	11.9 5.4
6 x 3 150 x 80	300 20	3.50 89	4.33 110	5.50 140	3.86 98	10.07 256	5.39 137	5/8 x 5 5/16 M16 x 135	13.2 6.0
6 x 4 150 x 100	300 20	4.50 114	4.21 107	5.50 140	3.86 98	10.07 256	6.46 164	5/8 x 5 5/16 M16 x 135	14.5 6.6
8 x ½ 200 x 15	300 20	2.75 70	5.31 135	5.82 148	4.72 120	12.87 327	4.4 112	¾ x 4¾ M20 x 120	12.5 5.7
8 x 1 200 x 25	300 20	2.75 70	5.31 135	5.98 152	4.72 120	12.87 327	4.4 112	¾ x 4¾ M20 x 120	12.5 5.7
8 x 1¼ 200 x 32	300 20	2.75 70	5.31 135	5.98 152	4.72 120	12.87 327	3.98 101	¾ x 4¾ M20 x 120	12.5 5.7
8 x 1½ 200 x 40	300 20	2.75 70	5.31 135	5.98 152	4.72 120	12.87 327	3.98 101	¾ x 4¾ M20 x 120	12.5 5.7
8 x 2 200 x 50	300 20	2.75 70	5.31 135	6.54 166	4.72 120	12.87 327	3.98 101	¾ x 4¾ M20 x 120	13.6 6.2
8 x 2½ 200 x 65	300 20	2.75 70	5.39 137	6.54 166	4.72 120	12.87 327	4.09 104	¾ x 4¾ M20 x 120	13.9 6.3
8 x 3 200 x 80	300 20	3.50 89	5.35 136	6.54 166	4.72 120	12.87 327	5.04 128	¾ x 4¾ M20 x 120	15.6 7.1
8 x 4 200 x 100	300 20	4.50 114	5.24 133	6.54 166	4.72 120	12.87 327	6.46 164	¾ x 4¾ M20 x 120	17.6 8.0

1. F Hole diameters listed are suggested hole diameters.
2. ‡T: Take-Out (Center of run to end of pipe to be engaged.)
3. \*Working pressure is based on standard wall carbon steel pipe.

**MATERIAL SPECIFICATIONS**

• **Housing:**

Ductile Iron to ASTM A536, Gr. 65-45-12 and or ASTM A395, Gr. 65-45-15, min. tensile strength 65,000 psi (448 MPa).

• **Surface Finish:**

- Orange color painted or red RAL3000 color painted.
- Hot dip galvanized (Option).
- Epoxy coated in red RAL3000 or other colors (Option)

• **Rubber Gasket:**

**Grade “E” EPDM** (Color code: Green stripe) Good for cold & hot water up to +230°F (+110°C). Also good for services for water with acid, water with chlorine, deionized water, seawater and waste water, dilute acids, oil-free air and many chemicals. **Not recommended for petroleum oils, minerals oils, solvents and aromatic hydrocarbons.**  
 Maximum Temperature Range: -30°F (-34°C) to +230°F (+110°C)\*.  
 \*EPDM gaskets for water services are not recommended for

steam services unless couplings or components are accessible for frequent gasket replacement.

- Grade “T” Nitrile** (Color code: Orange stripe) (Option) Recommended for petroleum products, vegetable oils, mineral oils and air with oil vapors. Temperature range: -20°F to +180°F (-29°C to +82°C). Also good for water services under +150°F (+66°C). **Do not use for HOT WATER above +150°F (+66°C) or HOT DRY AIR above +140°F (+60°C)**
- Other options: Grade “O” Fluoro-Elastomer  
Grade “L” Silicone.

• **Bolts & Nuts:**

Heat treated carbon manganese steel track bolts to ASTM A449-83a (or A183 Gr. 2), minimum tensile strength 110,000 psi (758 MPa), Zinc electroplated, with heavy-duty hexagonal nuts to ASTM A563.

**Flow Data –  
Cv Values**

Values for flow of water at +60°F (+16°C).

$$Cv = \frac{Q}{\sqrt{\Delta P}}$$

Where: Cv = Flow coefficient  
 Q = Flow (GPM)  
 ΔP = Pressure drop (psi)

Model 7721 Mechanical Tee, Female Threaded Outlet Cv Values			
Nominal Size in / mm	Cv Values	Nominal Size in / mm	Cv Values
½ 15	15	2 50	100
¾ 20	20	2½ 65	125
1 25	25	3 80	200
1¼ 32	45	4 100	350
1½ 40	60		

**Flow Characteristics**

Model 7721 Mechanical Tee, Female Threaded Outlet Flow Characteristics			
Nominal Size in / mm	Equivalent Length feet/meter of pipe	Nominal Size in / mm	Equivalent Length feet/meter of pipe
½ 15	2.0 0.6	2 50	10.0 3.2
¾ 20	4.0 1.2	2½ 65	20.0 6.0
1 25	5.0 1.5	3 80	27.0 8.1
1¼ 32	6.0 1.8	4 100	35.0 10.5
1½ 40	8.0 2.4		

## General Notes:

- **Maximum Working Pressure (CWP)** listed is the maximum cold water pressure for general piping services tested to ASTM F1476 and or AWWA C606 methods. Figures listed are based on roll- or cut-grooved standard wall carbon steel pipe. For other pipe schedules or pipe materials, contact **Shurjoint** for additional information.
- **Listed and or Approved Pressures** are pressure ratings for fire protection systems, tested and approved by various approval bodies. Please always refer to the latest approval data posted on the **Shurjoint** website.
- **Field Joint Test:** For one time only the system may be tested hydrostatically at 1½ times the maximum working pressure listed (AWWA C606 5.2.3).
- **Warning:** Piping systems must always be depressurized and drained before attempting disassembly and or removal of any components.
- **The 10 Year Limited Warranty** applies to manufacturing defects only and does not cover severe service/temperature applications or wear parts.
- **Shurjoint** reserves the right to change specifications, designs and or standard without notice and without incurring any obligations.

**Shurjoint** product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact **Shurjoint** Technical Service. **Shurjoint** reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligations to make such changes and modifications on **Shurjoint** products previously subsequently sold.